



[Web](#) [Images](#) [Groups](#) [News](#) [Froogle](#) [Local](#) [more »](#)

"HIGH BIT RATE FOUR PHASE MMIC REMC

[Advanced Search](#)
[Preferences](#)

Web Results 1 - 1 of 1 for "[HIGH BIT RATE FOUR PHASE MMIC REMODULATION DEMODULATOR AND MODULATOR](#)". (0.18 s)

Did you mean: "[HIGH BIT RATE FOUR PHASE MMIC **DEMODULATION** DEMODULATOR AND MODULATOR](#)"

[AMS Acta - New cold FET IQ linear vector modulator topology](#)

[High Bit Rate Four Phase MMIC Remodulation Demodulator and Modulator », GaAs 92](#)

[ESA/ESTEC Symposium, NOORDWIJK-The NETHERLANDS. ...](#)

[amsacta.cib.unibo.it/archive/00000315/ - 22k - \[Cached\]\(#\) - \[Similar pages\]\(#\)](#)

Did you mean to search for: "[HIGH BIT RATE FOUR PHASE MMIC **DEMODULATION** DEMODULATOR AND MODULATOR](#)"

Free! Google Desktop Search: Search your own computer. [Download now.](#)

Find: [emails](#) - [files](#) - [chats](#) - [web history](#) - [media](#) - [PDF](#)

"HIGH BIT RATE FOUR PHASE MM"

[Search within results](#) | [Language Tools](#) | [Search Tips](#) | [Dissatisfied? Help us improve](#)

[Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [About Google](#)

©2005 Google

ALMA MATER STUDIORUM
UNIVERSITÀ DI BOLOGNA[Alma-DL](#)[CIB Centro Inter-Bibliotecario](#) | [SBA Sistema Bibliotecario di Ateneo](#)Vai: [Collezioni Eprints](#)[Home](#) | [Cerca](#) | [Naviga](#)[Registrazione](#) | [Area di](#)Sei in: [AMS Acta](#) > New cold FET I-Q linear vector modulator topology

Boulanger, Cyrille e Lapierre, Luc e Gizard, Francis (2000) *New cold FET I-Q linear vector modulator topology*. In: Gallium Arsenide applications symposium. GAAS 2000, 2-6 october 2000, Paris.

Full text disponibile come:



[Documento PDF](#) - Necessita di [Adobe Acrobat Reader](#) o di una altro applicativo per la visualizzaione di file PDF.

Abstract

This paper presents the design, manufacture and test of a new cold FET monolithic I-Q vector modulator. The circuit has been developed in 8–8.4 GHz X band but can be transposed at any frequency range. The innovation is that the IF data signals are applied to the FET gates. The use of cold FETs allows achieving a 0.8 dB and 6° accuracy with only one voltage tuning on the whole bandwidth and the –25°C to +50°C temperature range. There is no DC consumption for the microwave modulator. The accuracy achieved at this first run is yet compatible with new coding and modulating systems and we have investigated several ways to improve the design.

Tipo di EPrint: Documento relativo ad una Conferenza o altro Evento (Poster)
Autori/Creatori: Boulanger, Cyrille e Lapierre, Luc e Gizard, Francis
Settori scientifico-disciplinari MIUR: [Area 09 - Ingegneria industriale e dell'informazione](#) > [ING-INF/01 Elettronica](#)
Strutture: [Società Scientifiche](#) > [GAAS](#)
Codice ID: 315
Depositato da: [CIB Staff](#)
Depositato il: 17 Giugno 2004

[1] FLM Van den Bogaart, R Pyndiah, "a 10-14 GHz linear MMIC vector modulator with less than 0.1 dB and 0.8° amplitude and phase error" 1990 IEEE MTT-S Digest [SEEK](#)

[2] A. Primerose, J. Graffeuil, L. Lapierre, J. Sombrin, J.C. Lalaurie, J. Larroque. « High Bit Rate Four Phase MMIC Remodulation Demodulator and Modulator », GaAs 92 ESA/ESTEC Symposium, NOORDWIJK-The NETHERLANDS. [SEEK](#)

[3] C. Boulanger, L. Lapierre, demande de brevet n°PCT/FR99/03276 « procede de modulation analogique et circuit integre monolithique a étage mélangeur comprenant des transistors à effet de champ non polarisés » [SEEK](#)

Solo per lo Staff dell Archivio: [Modifica questo record](#)